

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11)Publication number: **06042320 A**

(43)Date of publication of
application: **15.02.94**

(51)Int. Cl **F01L 3/12**
B23K 26/00
F01L 3/02
F01P 3/14
F02F 1/24

(21)Application number: **04198725**

(22)Date of filing: **24.07.92**

(71)Applicant: **TOYOTA MOTOR CORP**

(72)Inventor: **OZAWA HITOSHI**
TOKORO MASAMI
SASAKI KAZUHIKO
KAWASAKI MINORU

**(54)VALVE SEAT FOR INTERNAL
COMBUSTION ENGINE**

(57)Abstract:

PURPOSE: To easily mold a circulating path for cooling liquid and a valve seat having a clad sheet layer and further to more improve cooling performance by the clad sheet layer.

CONSTITUTION: A valve seat 16 comprises a cooling groove 17, closing member 18 and a clad sheet layer 19. The cooling groove 17 is drilled in a contact location of an intake valve 6 in a cylinder head 1. The cooling groove 17 is formed in a circular annular shape and opened toward a combustion chamber 2. The cooling groove 17 communicates with a cooling water introducing hole and a cooling water discharge hole 26. The closing member 18 closes an opening end of the cooling groove 17. A circulating path 21 for cooling water is formed between the closing member 18 and a wall surface of the cooling groove 17. The

clad sheet layer 19 is formed by padding in surface of the closing member 18 and a peripheral location of the cooling groove 17 by a laser clad method where metal powder is welded by using irradiation of laser light.

COPYRIGHT: (C)1994,JPO&Japio

